

Package: rgraph6 (via r-universe)

October 11, 2026

Version 2.0-5

Title Representing Graphs as 'graph6', 'digraph6' or 'sparse6' Strings

Depends R (>= 2.10)

Imports methods, Rcpp (>= 1.0.3)

LinkingTo Rcpp

Suggests testthat, knitr, rmarkdown, igraph (>= 2.0.0), network,
Matrix

Description Encode network data as strings of printable ASCII characters. Implemented functions include encoding and decoding adjacency matrices, edgelist, igraph, and network objects to/from formats 'graph6', 'sparse6', and 'digraph6'. The formats and methods are described in McKay, B.D. and Piperno, A (2014) <[doi:10.1016/j.jsc.2013.09.003](https://doi.org/10.1016/j.jsc.2013.09.003)>.

License GPL (>= 3)

RoxygenNote 7.2.1

Encoding UTF-8

LazyData true

Roxygen list(markdown=TRUE)

URL <https://mbojan.github.io/rgraph6/>

BugReports <https://github.com/mbojan/rgraph6/issues>

VignetteBuilder knitr

Repository <https://mbojan.r-universe.dev>

Date/Publication 2025-04-16 14:47:13 UTC

RemoteUrl <https://github.com/mbojan/rgraph6>

RemoteRef HEAD

RemoteSha faec1023098988454072e958f7f2305f3e5d0477

Contents

rgraph6-package	2
adjacency_from_text	3
as_digraph6	4
as_graph6	6
as_sparse6	7
choose_format	9
edgelist_from_text	10
from_digraph6	11
from_graph6	12
from_sparse6	14
graph_as_text	15
igraph_from_text	16
is_graph6	17
network_from_text	18
read_file6	19
sampleg6	19
Index	21

rgraph6-package	<i>rgraph6: Representing Graphs as 'graph6', 'digraph6' or 'sparse6' Strings</i>
-----------------	--

Description

Encode network data as strings of printable ASCII characters. Implemented functions include encoding and decoding adjacency matrices, edgelists, igraph, and network objects to/from formats 'graph6', 'sparse6', and 'digraph6'. The formats and methods are described in McKay, B.D. and Piperno, A (2014) [doi:10.1016/j.jsc.2013.09.003](https://doi.org/10.1016/j.jsc.2013.09.003).

Details

Formats 'graph6', 'sparse6' and 'digraph6' represent graphs as strings of printable ASCII characters. The formats are due to **Brendan McKay** who implemented them in his program Nauty (McKay 1978, 1980, 2003, McKay & Piperno 2014), and are described in detail [here](#). Package **rgraph6** is a native R implementation of these formats.

The main functions are `as_graph6()`, `as_digraph6()`, `as_sparse6()` for encoding network data and `igraph_from_text()` and `network_from_text()` for decoding. There are also other low-level functions to decode directly from `digraph6`, `graph6`, and `sparse6`.

Citation

When using this package please cite it by referring to the following publications: McKay B, Piperno A (2014). "Practical graph isomorphism, II." *Journal of Symbolic Computation*, 60, 94-112.

Bojanowski M, Schoch D (2021). *rgraph6: Representing Graphs as graph6, digraph6 or sparse6 Strings*. R package version: 2.0-0, <https://mbojan.github.io/rgraph6/>.

Call `citation(package="rgraph6")` for more details and the BibTeX entry.

Author(s)

Maintainer: Michal Bojanowski <michal2992@gmail.com> ([ORCID](#)) (Kozminski University)

Authors:

- David Schoch <david@schochastics.net> ([ORCID](#))

References

McKay, B. D. (1978) Computing automorphisms and canonical labellings of graphs *Combinatorial Mathematics, Lect. Notes Math.*, vol. 686, Springer-Verlag, Berlin, pp. 223-232 [doi:10.1007/BFb0062536](#)

McKay, B. D. (1981). Practical graph isomorphism. *Congressus Numerantium*, 30, pp. 45-87

McKay, B. D. (2003). "Nauty" User's Guide (version 2.2) (p. 112). Technical Report TR-CS-9002, Australian National University.

McKay, B. D., & Piperno, A. (2013). *Nauty and Traces user's guide* (Version 2.5). Computer Science Department, Australian National University, Canberra, Australia.

McKay, B. D., & Piperno, A. (2014). Practical graph isomorphism, II. *Journal of symbolic computation*, 60, 94-112. [doi:10.1016/j.jsc.2013.09.003](#)

See Also

Useful links:

- <https://mbojan.github.io/rgraph6/>
- Report bugs at <https://github.com/mbojan/rgraph6/issues>

adjacency_from_text	Create adjacency matrices from 'graph6', 'sparse6', or 'digraph6' symbols
---------------------	---

Description

Create adjacency matrices from 'graph6', 'sparse6', or 'digraph6' symbols

Usage

```
adjacency_from_text(object, ...)
```

Arguments

object	character vector of 'graph6', 'sparse6', or 'digraph6' symbols
...	other arguments, currently ignored

Details

If object contains 'sparse6' symbols, which are in fact encoded edgelist, the function will return corresponding adjacency matrices creating temporary igraph objects internally.

Value

A list of adjacency matrices.

Examples

```
# Graph6 symbols
sampleg6
adjacency_from_text(sampleg6)

# Sparse6 symbols
s6 <- c("DgXI@G~", "DgWCgCb")
adjacency_from_text(s6)

# Digraph6 symbol
d6 <- "&N???C??D?_G??C????_?C_?????C??Q@O?G?"
adjacency_from_text(d6)
```

as_digraph6

Encode network data as 'digraph6' symbols

Description

Generic function encoding directed networks as 'digraph6' symbol(s). See below for available methods.

Usage

```
as_digraph6(object)

## S3 method for class 'matrix'
as_digraph6(object)

## S3 method for class 'igraph'
as_digraph6(object)

## S3 method for class 'network'
as_digraph6(object)

## S3 method for class 'list'
as_digraph6(object)

## Default S3 method:
as_digraph6(object)
```

Arguments

object a matrix, an igraph object or a network object or a list thereof. See Methods section below.

Details

The 'digraph6' format is designed for directed graphs. Error is thrown in case it is given an undirected network.

Value

A character vector of 'digraph6' symbols.

Methods (by class)

- as_digraph6(matrix): Expects object to be a square matrix which is interpreted as an adjacency matrix of a directed graph.
- as_digraph6(igraph): Igraph object needs to be a directed graph. Requires **igraph** package.
- as_digraph6(network): Network object needs to be directed network. Requires **network** package.
- as_digraph6(list): If object is a list the function is applied to each element. Consequently, it can be a list with a mixture of supported objects classes (adjacency matrices, igraph, or network objects).
- as_digraph6(default): Throws an error about the unhandled class.

Examples

```
# From adjacency matrix -----
am <- matrix(c(
  0,1,0,
  0,0,1,
  1,0,0),
  byrow=TRUE, ncol=3, nrow=3)
as_digraph6(am)

# From igraph objects -----
if(requireNamespace("igraph", quietly=TRUE)) {
  g <- igraph::graph_from_adjacency_matrix(am)
  as_digraph6(g)
}

# From network objects -----
if(requireNamespace("network", quietly=TRUE)) {
  net <- network::network(am)
  as_digraph6(net)
}
```

as_graph6

Encode network data as 'graph6' symbols

Description

Generic function encoding undirected networks as 'graph6' symbol(s). See below for available methods.

Usage

```
as_graph6(object)

## S3 method for class 'matrix'
as_graph6(object)

## S3 method for class 'igraph'
as_graph6(object)

## S3 method for class 'network'
as_graph6(object)

## S3 method for class 'list'
as_graph6(object)

## Default S3 method:
as_graph6(object)
```

Arguments

object a matrix, an igraph object or a network object or a list thereof. See Methods section below.

Details

The 'graph6' format is designed for undirected graphs. Error is thrown in case it is given a directed graph.

Value

A character vector of 'graph6' symbols.

Methods (by class)

- `as_graph6(matrix)`: Expects object to be a square matrix which is interpreted as an adjacency matrix of an undirected graph. The function reads only the upper triangle of the matrix and there is no test whether the matrix is symmetric.

- `as_graph6(igraph)`: Igraph object needs to be an undirected graph. Requires **igraph** package.
- `as_graph6(network)`: Network object needs to be a directed network. Requires **network** package.
- `as_graph6(list)`: If object is a list the function is applied to each element. Consequently, it can be a list with a mixture of supported objects classes (adjacency matrices, igraph, or network objects).
- `as_graph6(default)`: The default method throws an error about an unhandled class.

Examples

```
# From adjacency matrix -----
am <- matrix(c(
  0,1,1,
  1,0,0,
  1,0,0
), byrow=TRUE, ncol=3)
as_graph6(am)

# From igraph objects -----
if(requireNamespace("igraph", quietly=TRUE)) {
  g <- igraph::graph_from_adjacency_matrix(am, mode = "undirected")
  as_graph6(g)
}

# From network objects -----
if(requireNamespace("network", quietly=TRUE)) {
  net <- network::network(am, directed=FALSE)
  as_graph6(net)
}
```

as_sparse6

Encode network data as sparse6 symbols

Description

Generic function encoding network data as 'sparse6' symbol(s). See below for available methods.

Usage

```
as_sparse6(object, ...)

## S3 method for class 'matrix'
as_sparse6(object, n = max(object, 0), ...)

## S3 method for class 'igraph'
as_sparse6(object, ...)
```

```
## S3 method for class 'network'
as_sparse6(object, ...)

## S3 method for class 'list'
as_sparse6(object, ...)

## Default S3 method:
as_sparse6(object, ...)
```

Arguments

object	an edgelist, igraph, or network object or a list thereof. See Methods section below.
...	other arguments passed to/from other methods
n	number of vertices in the graph

Value

A character vector of 'sparse6' symbols.

Methods (by class)

- `as_sparse6(matrix)`: Expects object to be a two-column matrix of *integers* which is interpreted as an edgelist of an undirected graph. By default the network size is inferred to be the maximal element of object. This can be overridden by providing the network size via the `n` argument, the results will not be identical though (see the Examples).
- `as_sparse6(igraph)`: Igraph object needs to be an undirected graph. Requires **igraph** package.
- `as_sparse6(network)`: Network object needs to be a directed network. Requires **network** package.
- `as_sparse6(list)`: If object is a list the function is applied to each element. Consequently, it can be a list with a mixture of supported objects classes (edgelist matrices, igraph, or network objects).
- `as_sparse6(default)`: The default method fails gracefully.

See Also

The 'sparse6' format is designed for undirected graphs. Error is thrown in case it is given a directed graph.

Examples

```
# From edgelist matrix -----
elm <- matrix(c(
  1, 2,
  2, 3,
  3, 4
```

```

), ncol=2, byrow=TRUE)
as_sparse6(elm) # 1--2, 2--3, 3--4
as_sparse6(elm + 6) # 1, 2, 3, 4, 5, 6, 7--8, 8--9, 9--10
as_sparse6(elm, n = 10) # 1--2, 2--3, 3--4, 5, 6, 7, 8, 9, 10

# From igraph objects -----
if(requireNamespace("igraph")) {
  g <- igraph::graph_from_edgelist(elm, directed=FALSE)
  as_sparse6(g)
}

# From network objects -----
if(requireNamespace("network")) {
  net <- network::network(elm, directed=FALSE)
  as_graph6(net)
}

```

choose_format

Choose most efficient format heuristically

Description

Given a graph suggest the most efficient format out of 'graph6', 'sparse6' or 'digraph6'.

Usage

```

choose_format(object, ...)

## Default S3 method:
choose_format(object, ...)

## S3 method for class 'list'
choose_format(object, ...)

```

Arguments

object	Igraph/network object or list thereof
...	other arguments, currently ignored

Details

If object is directed, the suggested format is 'digraph6'. If object is undirected the function suggests 'sparse6' if density is less than 0.15 and 'graph6' otherwise. This rule is approximate.

Value

Character value out of 'graph6', 'sparse6' or 'digraph6'. If object is a list, a vector of such values of the length equal to the length of object.

Examples

```
# From igraph -----
if(requireNamespace("igraph")) {
  g <- igraph::graph.famous("Zachary")
  choose_format(g)

  set.seed(123)
  glist <- list(
    igraph::sample_gnp(n = 15, p = 0.1),
    igraph::sample_gnp(n = 15, p = 0.2),
    igraph::sample_gnp(n = 15, p = 0.3),
    igraph::sample_gnp(n = 15, p = 0.15, directed = TRUE))

  choose_format(glist)
}

# From network -----
if(requireNamespace("network")) {
  m <- matrix(rbinom(25,1,.4),15,15)
  diag(m) <- 0
  g <- network::network(m, directed=FALSE)
  choose_format(g)
}
```

edgelist_from_text	Create edgelist matrices from 'graph6', 'sparse6', or 'digraph6' symbols
--------------------	--

Description

Create edgelist matrices from 'graph6', 'sparse6', or 'digraph6' symbols

Usage

```
edgelist_from_text(object, ...)
```

Arguments

object	character vector of 'graph6', 'sparse6', or 'digraph6' symbols
...	other arguments, currently ignored

Details

If object contains 'graph6' or 'digraph6' symbols, which are in fact encoded adjacency matrices, the function will return corresponding edgelist matrices creating temporary igraph objects internally.

Value

A list of edgelist matrices.

Examples

```
# Graph6 symbols
sampleg6
edgelist_from_text(sampleg6)

# Sparse6 symbols
s6 <- c(":DgXI@G~", ":DgWCgCb")
edgelist_from_text(s6)

# Digraph6 symbol
d6 <- "&N???C??D?_G??C????_?C_?????C??Q@O?G?"
edgelist_from_text(d6)
```

from_digraph6	<i>Parsing digraph6 symbols</i>
---------------	---------------------------------

Description

These functions take a vector of 'digraph6' symbols and return a list of other types of objects:

- [adjacency_from_digraph6\(\)](#) creates adjacency matrices
- [igraph_from_digraph6\(\)](#) creates 'igraph' objects. Requires package **igraph** to be installed.
- [network_from_digraph6\(\)](#) creates 'network' objects. Requires package **network** to be installed.

Usage

```
adjacency_from_digraph6(d6)

igraph_from_digraph6(d6, ...)

network_from_digraph6(d6, ...)
```

Arguments

```
d6          character vector of 'digraph6' symbols
...          other arguments, see Details.
```

Details

For [igraph_from_digraph6\(\)](#) additional arguments are passed to [igraph::graph_from_adjacency_matrix\(\)](#)

For [network_from_digraph6\(\)](#) additional arguments are passed to [network::as.network\(\)](#)

Value

The returned object is:

- for `adjacency_from_digraph6()`, a list of the same length as its input of square symmetric adjacency matrices.
- for `igraph_from_digraph6()`, a list of 'igraph' objects
- for `network_from_digraph6()`, a list of 'network' objects

See Also

`as_digraph6()` for encoding objects as 'digraph6' symbols.

Examples

```
am <- matrix(rbinom(16, 1, 0.3), 4, 4)
d6 <- as_digraph6(am)

# To adjacency matrix -----
adjacency_from_digraph6(d6)

# To igraph objects -----
if(requireNamespace("igraph", quietly=TRUE)) {
  igraph_from_digraph6(d6)
}

# To network objects -----
if(requireNamespace("network", quietly=TRUE)) {
  network_from_digraph6(d6)
}
```

from_graph6

Functions parsing 'graph6' symbols

Description

These functions take a vector of 'graph6' symbols and return a list of other types of objects:

- `adjacency_from_graph6()` creates adjacency matrices
- `igraph_from_graph6()` creates 'igraph' objects. Requires package **igraph** to be installed.
- `network_from_graph6()` creates network objects. Requires package **network** to be installed.

Usage

```
adjacency_from_graph6(g6)

igraph_from_graph6(g6, ...)

network_from_graph6(g6, ...)
```

Arguments

g6 character vector of 'graph6' symbols
 ... other arguments, see Details.

Details

For `igraph_from_graph6()` additional arguments are passed to `igraph::graph_from_adjacency_matrix()`

For `network_from_graph6()` additional arguments are passed to `network::as.network()`

Value

The returned object is:

- for `adjacency_from_graph6()`, a list of the same length as its input of square symmetric adjacency matrices.
- for `igraph_from_graph6()`, a list of 'igraph' objects
- for `network_from_graph6()`, a list of network objects

See Also

`as_graph6()` for saving objects as 'graph6' symbols.

Examples

```
A <- matrix(c(0,1,0,1,
              1,0,1,0,
              0,1,0,1,
              1,0,1,0), 4, 4, byrow = TRUE)
g6 <- as_graph6(A)

# To adjacency matrix -----
adjacency_from_graph6(g6)

# To igraph objects -----
if(requireNamespace("igraph", quietly=TRUE)) {
  igraph_from_graph6(g6)
}

# To network objects -----
if(requireNamespace("network", quietly=TRUE)) {
```

```

    network_from_graph6(g6)
}

```

from_sparse6

Parsing 'sparse6' symbols

Description

These functions take a character vector of 'sparse6' symbols and return a list of other types of objects:

- `edgelist_from_sparse6()` creates edgelist matrices
- `igraph_from_sparse6()` creates 'igraph' objects. Requires package **igraph** to be installed.
- `network_from_sparse6()` creates 'network' objects. Requires package **network** to be installed.

Usage

```
edgelist_from_sparse6(s6)
```

```
igraph_from_sparse6(s6)
```

```
network_from_sparse6(s6)
```

Arguments

`s6` character vector of 'sparse6' symbols

Value

The returned object is:

- for `edgelist_from_sparse6()`, a list of the same length as its input of two-column edgelist matrices. The matrix has a `gorder` attribute storing the number of vertices in the graph.
- for `igraph_from_sparse6()`, a list of 'igraph' objects
- for `network_from_sparse6()`, a list of 'network' objects

See Also

`as_sparse6()` for encoding network data objects as 'sparse6' symbols.

Examples

```
elm <- structure(c(1, 1, 2, 2, 4, 4, 5, 6, 9, 10, 7, 8, 4, 8, 6, 8,
  8, 5, 4, 6), .Dim = c(10L, 2L))
s6 <- as_sparse6(elm, n = 10)

# To edgelist matrix -----
edgelist_from_sparse6(s6)

# To igraph object -----
if(requireNamespace("igraph", quietly=TRUE)) {
  igraph_from_sparse6(s6)
}

# To network object -----
if(requireNamespace("network", quietly=TRUE)) {
  network_from_sparse6(s6)
}
```

graph_as_text	<i>Encode graph as text</i>
---------------	-----------------------------

Description

Encode a graph as 'graph6', 'sparse6' or 'digraph6' choosing the format automatically.

Usage

```
graph_as_text(object, ...)

## Default S3 method:
graph_as_text(object, ...)

## S3 method for class 'list'
graph_as_text(object, ...)
```

Arguments

object	igraph/network object or a list thereof
...	other arguments, currently ignored

Details

If object is a list it may be a mixture of 'network' and 'igraph' objects.

Value

A character vector of encoded graphs.

Methods (by class)

- `graph_as_text(default)`: The default method chooses the encoding format automatically using `choose_format()`.
- `graph_as_text(list)`: The list method applies the default method to each element.

See Also

[choose_format\(\)](#)

Examples

```
# From igraph -----
if(requireNamespace("igraph")) {
  g <- igraph::graph.famous("Zachary")
  graph_as_text(g)

  glist <- list(
    igraph::sample_gnp(n = 15,p = 0.1),
    igraph::sample_gnp(n = 15,p = 0.2),
    igraph::sample_gnp(n = 15,p = 0.3))

  graph_as_text(glist)
}

# From network -----
if(requireNamespace("network")) {
  m <- matrix(rbinom(25,1,.4),5,5)
  diag(m) <- 0
  g <- network::network(m, directed=FALSE)
  graph_as_text(g)
}
```

`igraph_from_text`

Create igraph objects from 'graph6', 'sparse6', or 'digraph6' symbols

Description

Create igraph objects from 'graph6', 'sparse6', or 'digraph6' symbols

Usage

```
igraph_from_text(object)
```

Arguments

`object` character vector of 'graph6', 'sparse6', or 'digraph6' symbols

Value

A list of 'igraph' objects.

Examples

```
if(requireNamespace("igraph", quietly=TRUE)) {
  # Graph6 symbols
  sampleg6
  igraph_from_text(sampleg6)

  # Sparse6 symbols
  s6 <- c("DgXI@G~", "DgWCgCb")
  igraph_from_text(s6)

  # Digraph6 symbol
  d6 <- "&N???C??D?_G??C?????_?C??????C??Q@O?G?"
  igraph_from_text(d6)
}
```

is_graph6

*Infer or test for graph6, sparse6, and digraph6 symbols***Description**

Functions `is_graph6()`, `is_sparse6()`, and `is_digraph6()` test if elements of a character vector are valid symbols of particular type.

Function `guess_format()` tries to guess the type of the symbols used in x.

Usage

```
is_graph6(x)

is_sparse6(x)

is_digraph6(x)

guess_format(x)
```

Arguments

x character vector

Value

Logical vector of length equal to `length(x)` with TRUE if an element is a valid symbol and FALSE otherwise.

Function `guess_format()` returns a character vector of the same length as x with values "graph6", "sparse6", or "digraph6" depending on the type of symbol present, or NA if the symbol is unknown or matches more than one type.

Note

At this moment the test is performed using regular expressions. Theoretically it may result in false positives.

Examples

```
all(is_graph6(g6))
all(is_sparse6(s6))
all(is_digraph6(d6))

# Vector mixing graphs in various formats
x <- g6
x[seq(2, 20, by = 3)] <- s6[seq(2, 20, by = 3)]
x[seq(3, 20, by = 3)] <- d6[seq(3, 20, by = 3)]
guess_format(x)
```

network_from_text	<i>Create network objects from 'graph6', 'sparse6', or 'digraph6' symbols</i>
-------------------	---

Description

Create network objects from 'graph6', 'sparse6', or 'digraph6' symbols

Usage

```
network_from_text(object)
```

Arguments

object character vector of 'graph6', 'sparse6', or 'digraph6' symbols

Value

A list of 'network' objects.

Examples

```
# complete graph in graph6 format
g6 <- "G~~~~{"

# random graph with 15 nodes
s6 <- "NeF?bsl?aNC"

# random directed graph with 10 nodes
d6 <- "&I???GGGI?_gG??O???"

network_from_text(g6)
network_from_text(c(g6,s6,d6))
```

read_file6	<i>Read files of 'graph6', 'sparse6' or 'digraph6' symbols</i>
------------	--

Description

Read files of 'graph6', 'sparse6' or 'digraph6' symbols

Usage

```
read_file6(path, type = "adjacency")
```

Arguments

path	character; path to file name
type	character; one of "adjacency", "edgelist", "igraph", or "network". Type of result returned.

Details

File pointed to by path is a text file with one graph symbol per line. Optional headers of the form >>graph6<< or >>sparse6<< in the first line (and without the newline after the header) are ignored and removed.

Value

A list of decoded graphs in the form of objects determined by type.

Examples

```
g6_file <- tempfile()
write(sampleg6,g6_file)
read_file6(g6_file, type = "adjacency")
unlink(g6_file)
```

sampleg6	<i>Example vectors of 'graph6', 'sparse6', and 'digraph6' codes</i>
----------	---

Description

Objects g6, s6, and d6 are vectors of codes in 'graph6', 'sparse6', and 'digraph6' representations respectively. Object sampleg6 is a vector of 'graph6' codes.

Usage

g6

s6

d6

sampleg6

Format

The three objects g6, s6, and d6 are character vectors of length 20 corresponding to undirected (in case of g6 and s6) and directed (in case of d6) graphs of varying sizes and densities.

Object sampleg6 is a character vector of length 9 of undirected graphs in 'graph6' format.

Details

Graphs in g6, s6, and d6 objects were generated using the common algorithm which consists of the following steps:

1. For each value from the vector of sizes of the node set (15, 30, 60, 120)...
2. ... generate a vector of edge counts (size of the edge set) of length 5 ranging from a single edge up to an edge count corresponding to the density of 0.2.
3. Given the node set sizes (item 1) and edge set sizes (item 2) sample undirected graphs from GNM model.
4. These undirected graphs are encoded in g6 and s6
5. Directed graphs were created by turning undirected edges to directed arcs in an arbitrary manner. These are encoded in the d6 object.

Index

- * **datasets**
 - sampleg6, [19](#)
- * **package**
 - rgraph6-package, [2](#)
 - _PACKAGE (rgraph6-package), [2](#)
- adjacency_from_digraph6
 - (from_digraph6), [11](#)
- adjacency_from_digraph6(), [11](#), [12](#)
- adjacency_from_graph6 (from_graph6), [12](#)
- adjacency_from_graph6(), [12](#), [13](#)
- adjacency_from_text, [3](#)
- as_digraph6, [4](#)
- as_digraph6(), [2](#), [12](#)
- as_graph6, [6](#)
- as_graph6(), [2](#), [13](#)
- as_sparse6, [7](#)
- as_sparse6(), [2](#), [14](#)
- choose_format, [9](#)
- choose_format(), [16](#)
- d6 (sampleg6), [19](#)
- digraph6, [2](#)
- edgelist_from_sparse6 (from_sparse6), [14](#)
- edgelist_from_sparse6(), [14](#)
- edgelist_from_text, [10](#)
- from_digraph6, [11](#)
- from_graph6, [12](#)
- from_sparse6, [14](#)
- g6 (sampleg6), [19](#)
- graph6, [2](#)
- graph_as_text, [15](#)
- guess_format (is_graph6), [17](#)
- guess_format(), [17](#)
- igraph::graph_from_adjacency_matrix(),
[11](#), [13](#)
- igraph_from_digraph6 (from_digraph6), [11](#)
- igraph_from_digraph6(), [11](#), [12](#)
- igraph_from_graph6 (from_graph6), [12](#)
- igraph_from_graph6(), [12](#), [13](#)
- igraph_from_sparse6 (from_sparse6), [14](#)
- igraph_from_sparse6(), [14](#)
- igraph_from_text, [16](#)
- igraph_from_text(), [2](#)
- is_digraph6 (is_graph6), [17](#)
- is_digraph6(), [17](#)
- is_graph6, [17](#)
- is_graph6(), [17](#)
- is_sparse6 (is_graph6), [17](#)
- is_sparse6(), [17](#)
- network::as.network(), [11](#), [13](#)
- network_from_digraph6 (from_digraph6),
[11](#)
- network_from_digraph6(), [11](#), [12](#)
- network_from_graph6 (from_graph6), [12](#)
- network_from_graph6(), [12](#), [13](#)
- network_from_sparse6 (from_sparse6), [14](#)
- network_from_sparse6(), [14](#)
- network_from_text, [18](#)
- network_from_text(), [2](#)
- read_file6, [19](#)
- rgraph6 (rgraph6-package), [2](#)
- rgraph6-package, [2](#)
- s6 (sampleg6), [19](#)
- sampleg6, [19](#)
- sparse6, [2](#)